



TRUCK

## Truck tyre changer MS 70

Universal fitting technology up to 26" rim diameter | up to a wheel width of 800 mm | adjustable hydraulic pressure and clamping force

Article number: 1 694 200 070

## Description

- The technical design of the MS 70 allows easy fitting of all tyres to a maximum wheel width of 800 mm.
- The bi-directional robust wheel clamping device ensures a high degree of safety when fitting and dismantling wheel assemblies.
- The hydraulic pressure arm maintains exceptional movement during the process. These are features of Beissbarth products which universally acclaimed as innovative as well as practical.

### Sturdy jaw clamp

- Each wheel is firmly held by four clamping jaws. The clamping jaws allows bi-direction of the device for easy removal and fitting of tyres. These features bring reliability and robustness as part of the Beissbarth approach to technology.

### Practical details

- The pressure roller can be turned to two positions and locked. This makes breaking of tyre beads easier. The fitting hook is used for wheels with tubes or commercial vehicles.

## Technical Data

Wheel diameter max.	1640 mm
Bead breaker force	3100 kg
Weight	593 kg
Rim diameter max.	26 "
Wheel width max.	800 mm
Wheel weight max.	1200 kg
Depth	1400 mm
Height	1240 mm
Power supply	3 x 400 V   50 - 60 Hz
Width	1640 mm
Rim diameter min.	14 "

## Accessories

1 695 300 099	Rim clamp for aluminium rims
1 695 400 139	Protection jaws for aluminium rims   26"   4 pcs.
1 695 300 102	Roller for tubeless tyres   for all truck tyre changers
1 694 302 032	Inflation Cage   for truck tyres
1 695 700 052	Electronic inflation computer   for tyre inflation cage
1 695 700 051	Tubeless Inflation Device   for inflation cage
1 695 103 526	Pneumatic Bead Depressor   for truck tyre changers MS 70/75/78/80
1 695 300 098	Split ring wheel clamp   for OTR (Off-the-road) wheels
1 695 300 094	Bead lifting lever   for truck tyre changers