



BASIC SERVICE

## Passenger car tyre changer MS 63 S (B) 400/3/50

Basic version with 20" turntable, tilt back pole, 1 speed

Article number: 1 694 201 369

## Description

- The MS 63 S only knows one speed: Go Fast.
- Equipped with a 20" turntable, the MS 63 S is the ideal entry solution for performing basic tyre services.

This version does not contain any plastic protection parts and is not ready for connecting and inflation system for tubeless tyres.

## Technical Data

Wheel diameter max.	1000 mm
Bead breaking range	65 - 300 mm
Compressed air connection	8 - 10 bar
Weight	240 kg
Rim width max.	11 "
Depth	1810 mm
Height	1960 mm
Power supply	400 V   50 Hz
Width	1270 mm
Rotation speed	7,5 rpm
Phases	3
Rim width min.	3 "
Min. inner clamping range	12 "
Max. inner clamping range	23 "
Min. outer clamping range	10 "
Max. outer clamping range	20 "

## Accessories

1 695 106 190	Roller board   for MS 63 S, MS 5x0 S, MS 6x0 S
1 695 103 210	Mounting head kit for motorbikes   for MS 5x0 S and MS 6x0 S
1 695 101 575	Motorbike / Scooter adaptors for MS 530S, MS 630S, MS 650S   4 pcs.
1 695 103 542	Scooter adaptors for MS 500S und MS 63S   4 pcs.
1 695 101 518	Bead breaking spacer for motorbike wheels   for MS 5x0 S, MS 63 S, MS 630 S, MS 650 S
1 695 102 725	Protective cover for mounting tool   left   for MS 5x0 S, MS 63 S, MS 630 S, MS 650 S
1 695 101 608	Protective cover for mounting tool   5 pcs.   for MS 5x0 S, MS 63 S, MS 630 S, MS 650 S
1 695 106 152	Shovel protection for bead breaker   for MS 5x0 S, MS 630 S, MS 650 S

S

---

1 695 101 402	Jaws plastic protection   4 pcs.   for MS 500 S and MS 63 S
---------------	---

---

1 695 103 211	Plastic mounting head kit   for MS 5x0 S, MS 63 S, MS 630 S, MS 650
---------------	---

---

S

---

1 695 108 913	Blast Inflating System   for MS5xx S, MS63 S, and MS6xx S
---------------	---

---

1 695 105 191	Plastic rim protection
---------------	------------------------

---

1 695 911 204	Pneumatic assistance arm Tecnoroller   for MS 63 S
---------------	--

---